according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Enke Arctic Seal 1K LF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Emergency sealing

1.3. Details of the supplier of the safety data sheet

Company name: ENKE-Werk Johannes Enke GmbH & Co. KG

Street: Hamburger Str. 16

Place: D-40221 Düsseldorf - Germany

Telephone: +49(0)211/ 30 40 74 Telefax: +49(0)211/ 39 37 18

e-mail: info@enke-werk.de
e-mail (Contact person): labor@enke-werk.de
Internet: www.enke-werk.de/en

Responsible Department: On weekdays between 7 a.m. and 4 p.m. +49 (0) 211/ 30 40 74

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0) 6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

GB CLP Regulation

Special labelling of certain mixtures

EUH208 Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane, N-(3

 $\hbox{-(trimethoxysilyl)} propyl) ethylene diamine, octhilinone (ISO); 2-octyl-2H-isothiazol-3-one;$

[OIT]. May produce an allergic reaction. Safety data sheet available on request.

EUH210 Safety data sheet ava

2.3. Other hazards

The product hydrolyses quickly in the presence of water to: Polymers and Methanol (CAS 67-56-1).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of silane-terminated polyurethanes and fillers

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 2 of 8

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
2768-02-7	trimethoxyvinylsilane; trimethoxy(vi		< 1 %	
	220-449-8	014-049-00-0		
	Skin Sens. 1B; H317			
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine			< 1 %
	217-164-6		01-2119970215-39	
	Eye Dam. 1, Skin Sens. 1B, STOT			
23432-65-7	[(Dimethoxymethylsilyl)methyl]carbaminsäuremethylester			< 1 %
	457-690-5		01-0000019371-74	
	Repr. 2; H361fd			
	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			< 1 %
			01-2119491304-40	
	Repr. 2, Skin Sens. 1A, Aquatic Ac	7 H400 H410		
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]			< 0,1 %
	247-761-7	613-112-00-5		
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
26530-20-1	247-761-7	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]	< 0,1 %
	inhalation: ATE 0,27 mg/l (dusts or mists); dermal: ATE 311 mg/kg; oral: ATE 125 mg/kg Skin Sens. 1A; H317: >= 0,0015 - 100 Aquatic Acute 1; H400: M=100 Aquatic Chronic 1; H410: M=100		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Methanol (CAS 67-56-1) is readily and rapidly absorbed at all exposure routes and is

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 3 of 8

toxic by all routes. Methanol may cause irritation of the mucosa, as well as nausea, vomiting, headaches, vertigo and visual disorders, including blindness (irrevers ible damage to the optic nerve), acidosis, spasms, narcosis and coma. There may be a delay in the onset of these effects after exposure.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Water mist, Extinguishing powder, alcohol resistant foam, Carbon dioxide, Sand.

5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire may be liberated: Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Avoid contact with eyes and skin. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Special danger of slipping by leaking/spilling product. Keep away from clothing as well as other incompatible materials. (SECTION 10: Stability and reactivity)

Advice on protection against fire and explosion

The product hydrolyses quickly in the presence of water to: Polymers and Methanol (CAS 67-56-1). Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

No special measures are necessary.

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 4 of 8

Further information on storage conditions

Protect from moisture. Keep/Store only in original container.

7.3. Specific end use(s)

Emergency sealing

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

The product hydrolyses quickly in the presence of water to: Polymers and Methanol (CAS 67-56-1)

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Our recommendation is as follows: Suitable materials for prolonged, direct contact (at least protection index 6, corresponding to > 480 minutes permeation time according to EN 374): Neoprene®, Viton®, PVC, butyl or nitrile rubber. Dispose of contaminated gloves. With proper, optimized operation, only short-term contact and liquid splashes are to be expected, therefore, according to DGUV Information 212-007, a glove with a minimum protection class of 1 (<10 min permeation time) is sufficient. It must be ensured that the gloves are changed at short notice in case of chemical contact.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: pasty Colour: grey

Odour: like: Menthol

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not determined

boiling range:

Flash point: 132 °C

Flammability

Solid/liquid: not applicable

not applicable

Lower explosion limits:

Upper explosion limits:

not determined

not determined

Self-ignition temperature

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 5 of 8

Solid: not applicable Gas: not applicable Decomposition temperature: not determined pH-Value: not determined

Viscosity / dynamic: 3 000 000 - 4 000 000 mPa·s pasty

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 23 °C):

Relative vapour density:

not determined

1,27 g/cm³

not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Reacts with: Water, Acid and Base. Formation of: Methanol (CAS 67-56-1)

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 6 of 8

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]				
	oral	ATE 125 mg/kg			
	dermal	ATE 311 mg/kg			
	inhalation dust/mist	ATE 0,27 mg/l			

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

Further information

May produce an allergic reaction.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Adhering to the official regulations, it can be disposed of in appropriate incinerator. Cured residual material can

be disposed of with household waste.

Disposal of packaging:

Containers have to be emptied completely and free of drops after final product removal. Emptied packages can be returned to the partners of Kreislaufsystem Blechverpackungen Stahl (Recycling system for metal containers).

Collection points are provided by the ENKE company as user of the mark.

List of Wastes Code - residues/unused products

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 7 of 8

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE. FORMULATION. SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

according to UK REACH Regulation



Enke Arctic Seal 1K LF

Revision date: 20.12.2022 Page 8 of 8

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

EUH208 Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane, N-(3

-(trimethoxysilyl)propyl)ethylenediamine, octhilinone (ISO); 2-octyl-2H-isothiazol-3-one;

[OIT]. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The current version of this safety data sheet is available on our website www.enke-werk.de/en

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)