



# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 2 of 9

### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P271	Use only outdoors or in a well-ventilated area.
P331	Do NOT induce vomiting.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

polymer solution in xylene

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	Xylene			85 - < 90 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
1330-20-7	215-535-7	Xylene	85 - < 90 %	
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg			

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Take off immediately all contaminated clothing and wash it before reuse.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

Take up mechanically. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Aspiration hazard! Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 3 of 9

### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Do NOT induce vomiting. Aspiration hazard!

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Powder, Foam, Water spray jet, Carbon dioxide (CO<sub>2</sub>).

### **5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide; Carbon dioxide (CO<sub>2</sub>); Gases/vapours, harmful.

### **5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks,

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 4 of 9

open flames and other ignition sources. No smoking.

### 7.3. Specific end use(s)

2-component Primer / Adhesion promotor

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Our recommendation is as follows: Suitable materials for prolonged, direct contact (at least protection index 6, corresponding to > 480 minutes permeation time according to EN 374): Neoprene®, Viton®, PVC, butyl or nitrile rubber. Dispose of contaminated gloves. With proper, optimized operation, only short-term contact and liquid splashes are to be expected, therefore, according to DGUV Information 212-007, a glove with a minimum protection class of 1 (<10 min permeation time) is sufficient. It must be ensured that the gloves are changed at short notice in case of chemical contact.

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Fresh air mask. Short term filler device: A2 - P2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	transparent , light yellow
Odour:	like: Xylene

#### Changes in the physical state

Melting point/freezing point: not determined

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 5 of 9

Boiling point or initial boiling point and boiling range: ~ 140 °C

Flash point: ~ 30 °C

### Flammability

Solid/liquid: not applicable

Lower explosion limits: 1,0 vol. %

Upper explosion limits: 8,0 vol. %

Auto-ignition temperature: ~ 480 °C

### Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

pH-Value: not determined

Viscosity / dynamic:  
(at 20 °C) 20 - 30 mPa·s

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

### Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure:  
(at 20 °C) 0,5 - 1,0 hPa

Density (at 20 °C): 0,87 g/cm<sup>3</sup>

Relative vapour density: not determined

## 9.2. Other information

### Information with regard to physical hazard classes

Oxidizing properties  
Not oxidising.

### Other safety characteristics

Solid content: not determined

Evaporation rate: not determined

### Further Information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable, Ignition hazard.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 6 of 9

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Harmful in contact with skin.

Harmful if inhaled.

#### ATEmix calculated

ATE (dermal) 1294,1 mg/kg; ATE (inhalation vapour) 12,94 mg/l; ATE (inhalation dust/mist) 1,765 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	Xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (Xylene)

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Xylene)

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not: Ecotoxic.

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 7 of 9

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Containers have to be emptied completely and free of drops after final product removal. Emptied packages can be returned to the partners of Kreislaufsystem Blechverpackungen Stahl (Recycling system for metal containers).

Collection points are provided by the ENKE company as user of the mark.

#### **List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### **List of Wastes Code - used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1263
<b><u>14.2. UN proper shipping name:</u></b>	Paint
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3
Classification code:	F1
Special Provisions:	163 640E 650
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

### **Inland waterways transport (ADN)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1263
<b><u>14.2. UN proper shipping name:</u></b>	Paint
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 8 of 9

Classification code: F1  
Special Provisions: 163 640E 650  
Limited quantity: 5 L  
Excepted quantity: E1

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

#### Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# Safety Data Sheet

according to UK REACH Regulation



## Universal Primer 2K, Component A

Revision date: 07.12.2023

Page 9 of 9

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The current version of this safety data sheet is available on our website [www.enke-werk.de/en](http://www.enke-werk.de/en)

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*